

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
20 December 2001 (20.12.2001)

PCT

(10) International Publication Number  
**WO 01/97406 A2**

(51) International Patent Classification<sup>7</sup>: **H04B 7/185**

(21) International Application Number: PCT/US01/18587

(22) International Filing Date: 7 June 2001 (07.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/594,374 15 June 2000 (15.06.2000) US

(71) Applicant: **HUGHES ELECTRONICS CORPORATION** [US/US]; 200 North Sepulveda Boulevard, El Segundo, CA 90245 (US).

Verdes, CA 90275 (US). **LIM, Wah, L.**; 30 Canyon Fairway Drive, Newport Beach, CA 92660 (US). **FERIA, Ying**; 306 Anderson Street, Manhattan Beach, CA 90266 (US). **CHANG, Ming, U.**; 28815 Indian Valley Road, Rancho Palos Verdes, CA 90275 (US).

(74) Agents: **DURAI SWAMY, Vijayalakshmi, D. et al.**; Hughes Electronics Corporation, Bldg. 001, MS A109, P.O. Box 956, El Segundo, CA 90245 (US).


(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:  
— without international search report and to be republished upon receipt of that report

(72) Inventors: **CHANG, Donald, C., D.**; 2350 Moberly Court, Thousand Oaks, CA 91360 (US). **WANG, Weizheng**; 27113 Indian Peak Road, Rancho Palos

Verdes, CA 90275 (US). For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COMMUNICATION SYSTEM AS A SECONDARY PLATFORM WITH FREQUENCY REUSE



(57) Abstract: A communications system (10) and method of operating the communications system includes a first stratospheric platform generating a second beam having a frequency the same as a satellite beam to the same service area. User terminals are configured to receive the first beam or the second beam.

WO 01/97406 A2

**This Page Blank (uspto)**

### **Related Application**

The present application is related to U.S. Patent Application (Serial No. 09/594,375 filed June 15, 2000 ) entitled "Communication System Having Frequency Reuse In Non-Blocking Manner" filed simultaneously herewith and incorporated by reference hereby.

### **Technical Field**

5           The present invention relates generally to communications systems. and more particularly, to a system allowing frequency reuse with existing systems.

### **Background Art**

          In this communication age, content providers are increasingly investigating ways in which to provide more content to users as well as  
10   interfacing with users.

          Communication satellites have become commonplace for use in many types of communication services, e.g., data transfer, voice communications, television spot beam coverage, and other data transfer applications. As such, satellites transmit and receive large amounts of signals  
15   used in either a "bent pipe" or "spot array" configuration to transmit signals to desired geographic locations on the Earth.

          Because the frequency of resources are scarce for over-the-air transmission, various encoding schemes are used to provide a greater number of communication signals within an allocated communication band spectrum.  
20   Such encoding schemes include code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA),

or combination of these schemes. Further, to prevent interference the schemes may operate at various frequencies.

There is a continual need to provide new systems. However, if no spectrum is available typically potential system operators must forgo a pursuing a system.

It would therefore be desirable to provide a system that allows reuse of frequency spectrums allocated to other users.

### Summary Of The Invention

It is therefore one object of the invention to provide an improved communications system that allows frequency reuse. Another object of the invention is to provide a low cost communication system.

In one aspect of the invention, a method for operating a communication system comprises the steps of:

generating a first beam using a first frequency directed at a service area with a satellite; and

generating a second beam using the first frequency directed at the service area from a stratospheric platform.

In a further aspect of the invention, a communications system has a first stratospheric platform generating a beam having the same frequency as a satellite beam in the same area. User terminals are configured to receive the beam from the satellite and from the stratospheric platform.

One advantage of the invention is that the user terminals for existing systems may be reused. Another advantage of the system is that several users platforms reusing the same frequency spectrum may be used.

Other objects and features of the present invention will become apparent when viewed in light of the detailed description of the preferred embodiment when taken in conjunction with the attached drawings and appended claims.

### **Brief Description of the Drawings**

Figure 1 is a high level system diagram relative of a preferred embodiment in the invention to the Earth of a preferred embodiment in the invention.

5 Figure 2 is a plot illustrating various angles of the satellite systems according to Figure 1.

Figure 3 is a system diagram of a preferred embodiment in the invention.

Figure 4 is a plot of seven spot beams using three-color frequency reuse.

10 Figure 5 is a plot of six spot beams with two-color reuse.

### **Best Modes For Carrying Out The Invention**

In the following figures the same reference numerals are used to identify the same components in the various views.

The present invention is applicable to many communications systems including various mobile, fixed, point-to-point broadcast and other  
15 types of communications.

Referring now to Figure 1, the present invention is a communications system 10 that employs a stratospheric platform 12 positioned above Earth 14. Stratospheric platform 12 communicates with a user 16 positioned on Earth 14. A geosynchronous satellite 18 having a  
20 geosynchronous orbit 20 is also illustrated. The geosynchronous orbit 20 allows the geosynchronous satellite 18 to maintain a relatively fixed position above a particular point on the Earth. Although only one stratospheric platform 12 and

one geosynchronous orbit satellite 18 are illustrated, the present invention may include several of each.

As illustrated, the line of sight 22 of stratospheric platform 12 has a significantly different elevation angle than line-of-sight 24. As will be  
5 illustrated below, the line-of-sight corresponds to different elevation angles relative to user 16. The difference in line-of-sights 22,24 allows frequency reuse between geosynchronous satellite 18 and stratospheric platform 12.

Stratospheric platform 12 may comprise one of many types of proposed stratosphere based devices such as unmanned plane, balloons,  
10 dirigibles or the like. Stratospheric platform 12 preferably may also comprise a stratosphere-based platform such as those under development by AeroVironment. Helios is one such project being developed by AeroVironment. The Helios stratospheric platform is an unmanned vehicle that can fly for several months at an altitude of about 60,000 feet above the Earth.  
15 Helios is a solar powered electric plane that is modular in design and may be configured to carry a variety of payloads. Stratospheric platforms also deploy relatively rapidly compared to satellites and thus, if the need increases, the system capability may be increased or modified.

Referring now to Figure 2, stratospheric platform 12 is illustrated  
20 having an elevation angle  $E_1$  with respect to the user 16. Also, the azimuth angle  $A_1$  of stratospheric platform 12 is also illustrated. Azimuth angle  $A_1$  is the angle from north. Although different, the azimuth angle and elevation angle for a satellite 18 is equally applicable. Of course, the elevation angle and azimuth angle for stratospheric platform 12 will vary depending on its location  
25 that may vary depending on the stratospheric platform 12. Of course, the height of the stratospheric platform must also be taken in consideration.

Referring now to Figure 3, communications system 10 having a plurality of platforms 12A, 12B and 12C is used to cover a predetermined service area 26 on the Earth's surface. Although three are used for illustrative purposes, only one is required. A plurality of user terminals 28 are used to  
5 illustrate mobile users and fixed users respectively. Mobile user terminals 28M may comprise but are not limited to automotive applications, personal digital assistant applications, and cellular phone applications. Fixed user terminals 28F may, for example, comprise business-based or home-based communications systems. Each user terminal 28F, 28M may receive a signal with a  
10 predetermined signal strength or receive an antenna radiation spot in a spot beam pattern that is available from and provided by stratospheric platform 12.

Communications system 10 further includes a gateway station 30 that is coupled to terrestrial networks 32 and a device operations center 34. Both gateway station 30 and device operations center 34 are in communication  
15 with platforms 12. Gateway station 30 provides a link between user terminals 28F, 28M and terrestrial networks 32 through stratospheric platform 12.

Device operations center 34 provides command and control functions to platforms 12A-12C. Although illustrated as two separate units, gateway station 30 and device operations center 34 may be combined into the  
20 same physical location.

The platforms 12A-12C are used as a communications node for gateway station 30 and user terminals 28M and 28F, each of which have antennas that are pointed in the direction of the platform. The gateway antenna  
30A of gateway station 30 and user terminal antennas 28A has a beam width  
25 wide enough to maintain communication links with platform 12 throughout the flight path. The antennas 28A, 30A allow for large data throughput.



Platforms 12A-C each have a controller 36 that is used to control communications with the user terminals 28F, 28M. In the present invention, the controller 36 is used to generate a plurality of beams as is discussed below. The frequency of the beams may be within the spectrum of a geostationary satellite.

5 Various numbers of users may communicate within a beam.

Controller 36 may be a secondary payload for the platforms. That is, to reduce system expense, the controllers 36 may be secondary to a primary controller 38 for another type of system already carried on the platform. The selective size and weight of controller 36 relative to controller 38 may be  
10 kept small to reduce the burden on platform 12.

Referring now to Figure 4, a plurality of beams 40A-40G are illustrated as approximately circular in area 26. The circular area 26 defines an outer boundary defined where an interference level is tolerable. For example, the beams 40A-40G may be approximated at the 20-dB side load contour. As  
15 illustrated, three colors are used in the seven spot beams. That is, the center beam 40G is one frequency. Beams 40A, C, and E have a different frequency than beams 40B, D, F. Beams 40A-40F have a different frequency than beam 40G. In one preferred embodiment of the invention, the area 26 is preferably about 45 kilometers.

20 Gateway stations 42A-44D use one of the communications frequencies of beams 40A-40G to communicate with the platform 12.

Referring now to Figure 5, two frequencies are used. That is, beams 44A, 44C, and 44E have a different frequency than beams 44B, 44D, and 44F. As was illustrated in Figure 4, the center beam frequency is different than  
25 the outer frequencies. Therefore, an inefficiency in the system exists. It is therefore more efficient to remove the center beam frequency and provide the

gateway stations therein. In this manner, only two frequencies need be provided. Thus, the bandwidth of each channel may be extended. By providing the "hole" in the coverage, the highest system throughput may be obtained. In this manner, only three gateway stations 48A, 48B, and 48C are required.

5                   In one design configuration, broadband communication throughput is between about 1.75 to 3 GHz, because the payload is piggy-backed onto another application. This amount of throughput may be used to support a substantial number of users while maintaining low cost. For example, an E<sub>1</sub> line requires a data rate of 512 Kbps. In this manner, each platform may  
10 support 5600 users. If ten platforms are used and assuming a statistic factor of 100, the number of system users may approach 5.6 million.

                  In operation, the user terminals 28 preferably have directional antennas that allow pointing at different platforms 12. Both user links and feeder links share spectrum. Also, asymmetric track is used on forward links  
15 and return links. Advantageously, the spectrum for existing communications is reused which allows user terminals to be also reused, the implementation of such a system is believed to require a sufficiently lower cost than an independent frequency. This system may be used to augment existing geostationary applications. Also, the present application may also be used in a  
20 non-blocking manner to prevent the stratospheric platform from interfering with communications from the geostationary satellite. That is, signals in areas of conflict may not be broadcast.

                  While particular embodiments of the invention have been shown and described, numerous variations alternate embodiments will occur to those  
25 skilled in the art. Accordingly, it is intended that the invention be limited only in terms of the appended claims.

**What Is Claimed Is:**

- 1                   1.     A communication system for use with geosynchronous  
2     satellite systems broadcasting a first beam at a first frequency comprising:  
3                   a first stratospheric platform generating a second beam having  
4     the first frequency;  
5                   user terminals configured to receive the first beam and the  
6     second beam.
- 1                   2.     A system as recited in claim 1 wherein user terminals  
2     comprise directional antennas.
- 1                   3.     A system as recited in claim 1 further comprising a  
2     second stratospheric platform generating a third beam having the first  
3     frequency.
- 1                   4.     A system as recited in claim 3 wherein said user terminal  
2     receives signals from the first stratospheric platform and the second  
3     stratospheric platform.
- 1                   5.     A system as recited in claim 1 wherein the second beam  
2     is generated from a secondary payload.
- 1                   6.     A communication system for use with geosynchronous  
2     satellite systems broadcasting a first beam at a first frequency comprising:  
3                   a first stratospheric platform having a primary payload and a  
4     secondary payload, said secondary payload generating communication signals  
5     having the first frequency.

1                   7.     A system as recited in claim 6 further comprising a  
2 second stratospheric platform generating a third beam having the first  
3 frequency.

1                   8.     A system as recited in claim 6 wherein the second beam  
2 is generated from a secondary payload.

1                   9.     A method for operating a communications system  
2 comprising the steps of:

3                   generating a first beam using a first frequency directed at a  
4 service area with a satellite; and



5                   generating a second beam using the first frequency directed at  
6 the service area from a stratospheric platform.

1                   10.    A method as recited in claim 9 wherein said step of  
2 generating a second beam comprises the step of generating a second beam from  
3 a secondary payload.


1                   11.    A method as recited in claim 9 wherein said satellite  
2 comprises a geostationary satellite.

1                   12.    A method as recited in claim 9 further comprising the  
2 step of generating a feeder link.

1/3



**This Page Blank (uspto)**



**This Page Blank (uspto)**






FIG. 4




FIG. 5

**This Page Blank (uspto)**

RECEIVED

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

JUN 11 2002

PATENTS & LICENSING  
CORPORATE OFFICE  
World Intellectual Property Organization  
International Bureau(43) International Publication Date  
20 December 2001 (20.12.2001)

PCT

(10) International Publication Number  
WO 01/97406 A3(51) International Patent Classification<sup>7</sup>: H04B 7/185

(21) International Application Number: PCT/US01/18587

(22) International Filing Date: 7 June 2001 (07.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/594,374 15 June 2000 (15.06.2000) US

(71) Applicant: HUGHES ELECTRONICS CORPORATION [US/US]: 200 North Sepulveda Boulevard, El Segundo, CA 90245 (US).


Fairway Drive, Newport Beach, CA 92660 (US). **FERIA, Ying**: 306 Anderson Street, Manhattan Beach, CA 90266 (US). **CHANG, Ming, U.**: 28815 Indian Valley Road, Rancho Palos Verdes, CA 90275 (US).(74) Agents: **DURAI SWAMY, Vijayalakshmi, D.** et al.: Hughes Electronics Corporation, Bldg. 001, MS A109, P.O. Box 956, El Segundo, CA 90245 (US).

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:  
with international search report(88) Date of publication of the international search report:  
30 May 2002(72) Inventors: **CHANG, Donald, C., D.**: 2350 Moberly Court, Thousand Oaks, CA 91360 (US). **WANG, Weizheng**: 27113 Indian Peak Road, Rancho Palos Verdes, CA 90275 (US). **LIM, Wah, L.**: 30 Canyon

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FREQUENCY REUSE IN A GEOSYNCHRONOUS SATELLITE COMMUNICATION SYSTEM



(57) Abstract: A communications system (10) and method of operating the communications system includes a first stratospheric platform generating a second beam having a frequency the same as a satellite beam to the same service area. User terminals are configured to receive the first beam or the second beam.

WO 01/97406 A3

**This Page Blank (uspto)**

# INTERNATIONAL SEARCH REPORT

International Application No

PC1/US 01/18587

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 H04B7/185

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 13598 A (ANGEL TECHNOLOGIES CORP ; DIAMANDIS PETER H (US); ARNOLD MARC (US);) 18 March 1999 (1999-03-18) page 6, line 12 -page 8, line 20	1-3,5-12
X	WO 99 23769 A (RAYTHEON CO) 14 May 1999 (1999-05-14) page 6, line 15 -page 11, line 4 page 20, line 8 - line 17 --- -/--	1,2,5-12



Further documents are listed in the continuation of box C



Patent family members are listed in annex.

\* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

15 January 2002

Date of mailing of the international search report

21/01/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Larcinese, A

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/18587

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>COLELLA N J ET AL: "THE HALO NETWORKTM"</p> <p>IEEE COMMUNICATIONS MAGAZINE, IEEE SERVICE</p> <p>CENTER. PISCATAWAY, N.J, US,</p> <p>vol. 38, no. 6, June 2000 (2000-06), pages</p> <p>142-148, XP000932657</p> <p>ISSN: 0163-6804</p> <p>page 142, right-hand column, line 20 -</p> <p>line 30</p> <p>page 144, right-hand column, line 32 -page</p> <p>145, left-hand column, line 5</p> <p>page 146, right-hand column, line 59 -page</p> <p>147, left-hand column, line 11</p> <p>figures 1,3</p> <p>-----</p>	1,2,5-12

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/18587

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9913598	A	18-03-1999	AU	9380298 A	29-03-1999
			TW	421935 B	11-02-2001
			WO	9913598 A1	18-03-1999
<hr/>					
WO 9923769	A	14-05-1999	US	6061562 A	09-05-2000
			AU	1079399 A	24-05-1999
			EP	1027775 A1	16-08-2000
			JP	2001522191 T	13-11-2001
			WO	9923769 A1	14-05-1999
<hr/>					

**This Page Blank (uspto)**